

ATS Harness

Transfer Switch Connector Harness

The BTS Basic Transfer Switch harness is designed for quick and fault free connection between the basic transfer switch to the TSP transformer module and ATS controller. There are assorted length harness available or can be customized according to user requirement.

Specifications



Description	12P Harness		
Application	Connect BTS and TSP-01 Module, TSP-02 Module, TSP-04 Module or connect ATS Controller (CM0900) and BTS		
Part NO.	Length	Rated Volt	Housing
HU-081	810 mm	600 VAC	AMP 770022-1
HU-100	1000 mm	600 VAC	AMP 770022-1
HU-250-12	2500 mm	600 VAC	AMP 770022-1
HU-150	1500 mm	600 VAC	AMP 770022-1



Description	12P Harness Single Socket		
Application	1. Connect TSP-01 Module, TSP-02 Module and BTS or other Transfer Switch 2. Connect Kutai BTS and general ATS-380 Controller, CM0900 Controller and BTS or other Transfer Switch		
Part NO.	Length	Rated Volt	Housing
HU-093	930 mm	600 VAC	AMP 770022-1
HU-150-1	1500 mm	600 VAC	AMP 770022-1



Description	18P Harness		
Application	Connect ATS-01 Controller and TSP-01 Module, TSP-02 Module, TSP-04 Module		
Part NO.	Length	Rated Volt	Housing
HU-062	620 mm	300 VAC	DINKLE 2ESDPL-18P
HU-074	740 mm	300 VAC	DINKLE 2ESDPL-18P
HU-107	1070 mm	300 VAC	DINKLE 2ESDPL-18P
HU-250-18	2500 mm	300 VAC	DINKLE 2ESDPL-18P





Description	25cm and 43cm Harness		
Application	To connect TC-V2 Control Unit and TS2P125 / TS3P125 Switch when side by side connected on base plate		
Part NO.	Length	Rated Volt	Housing
HU-025-TS-12	200 mm	600 VAC	AMP-172170-1
HU-043-TS-12	430 mm	600 VAC	AMP-172170-1



Description	70cm Harness		
Application	To connect TC-V2 Control Unit when installed on enclosure door panel and TS2P125 / TS3P125 Switch fixed on base plate		
Part NO.	Length	Rated Volt	Housing
HU-070-TS-12	700 mm	600 VAC	AMP-172170-1

